


**PG-12V35 FR**      **12 Volt 36 AH @ 20-hr. rate**  
**35 AH @ 10-hr. rate**

**Rechargeable Sealed Lead Acid Battery**  
**Designed for Cyclic, Standby, and Solar Applications**






## Terminals (mm)

- T6: Threaded insert w. 6 mm stud fastener



## Physical Dimensions: in (mm)



**L: 7.72 (196) W: 5.10 (130) H: 6.22 (158) HT: 6.97 (177)**

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

## Features

- **Long Service Life** - Thick plate design and efficient gas recombination yield a service life expectancy of up to 10 years in standby mode.
- **Low Internal Resistance** - Superb high-rate discharge characteristics ensure reliable performance in UPS and Telecom applications.
- **Maintenance-Free, Non-Spillable** - Proven VRLA technology guarantees safe operation without maintenance and 'non-restricted article' status for transportation.
- **Handles** - Integral carrying handles.
- **Low Self-Discharge** - Lead-calcium alloy grids and use of high purity lead account for superior shelf-life characteristics permitting storage for extended periods of time.
- **Designed-In Reliability** - Cutting-edge manufacturing and process control combined with meticulous quality assurance procedures guarantee consistent and dependable performance.

## Performance Specifications

**Nominal Voltage** ..... 12 volts (6 cells)

**Nominal Capacity**

20-hr. (1.80A to 10.80 volts) .....	36.0 AH
10-hr. (3.5A to 10.80 volts) .....	35.0 AH
8-hr. (4.2A to 10.50 volts) .....	33.6 AH
5-hr. (6.50A to 10.50 volts) .....	32.5AH
3-hr. (10.00A to 10.50 volts) .....	30.0 AH
1-hr. (27.0A to 9.60 volts) .....	27.0 AH

**Approximate Weight** ..... 24.5 lbs. (11.1 kg)

**Energy Density (10-hr. rate)** ..... 1.72 W-h/in3 (104.66 W-h/l)

**Specific Energy (10-hr. rate)** ..... 17.00 W-h/lb (37.49 W-h/kg)

**Internal Resistance (approx.)** ..... 8.0 milliohms

**Max Short-Duration Discharge Current (10 Sec.)**..... 175 amperes

**Shelf Life (% of nominal capacity at 68°F (20°C))**

1 Month .....	97%
3 Months.....	91%
6 Months .....	83%

**Operating Temperature Range**

Charge.. ..... -4°F (-20°C) to 122°F (50°C)

Discharge..... -40°F (-40°C) to 140°F (60°C)


**Case** ..... ABS Plastic (UL94 V-0 flame retardant)

**Power-Sonic Chargers** .....PSC-124000A, 124000A-C


**Constant Current & Power Discharge Ratings**

MODEL	FINAL VOLTAGE	AMPS/WATTS PER CELL @ 25° C													
		5 MIN		10 MIN		15 MIN		20 MIN		30 MIN		45 MIN		60 MIN	
		A	W	A	W	A	W	A	W	A	W	A	W	A	W
<b>PG-12V35 FR</b>	1.80	124	240	84	162	66	128	54	105	42	80	31	60	25	49
	1.75	136	260	88	170	70	134	58	109	44	83	33	62	26	50
	1.67	148	274	98	182	76	143	62	117	46	86	35	64	27	51
	1.60	158	286	106	194	82	150	66	120	50	90	36	66	28	52


**Discharge Time vs. Discharge Current**



**Discharge Characteristics**



**Shelf Life & Storage**



**Charging**

**Cycle Applications:** Limit initial current to 10.5A. Charge until battery voltage (under charge) reaches 14.4 to 14.7 volts at 68°F (20°C). Hold at 14.4 to 14.7 volts until current drops to under 350mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to “float” voltage.

**“Float” or “Stand-By” Service:** Hold battery across constant voltage source of 13.5 to 13.8 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

**Note:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

**Chargers**

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for “C-Series Switch Mode Chargers” and “Transformer Type A and F Series”. Please contact our Technical department for advice if you have difficulty in locating suitable models.

**Further Information**

Please refer to our website [www.power-sonic.com](http://www.power-sonic.com) for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc..

